

# PERISTALTIC PUMP

## MP2-B 1 TIMER

Data  
Sheet

### DESCRIPTION

- ✓ Peristaltic pump with timer ON / OFF : adjustment from 0 to 25 seconds by trimmer
- ✓ Back plate panel with wall mounting bracket
- ✓ Reinforced PP body
- ✓ Polycarbonate front panel
- ✓ Standard Power Supply 230 Vac
- ✓ 100 % Made in Italy
- ✓ CE approved
- ✓ Small size
- ✓ Easy to install and minimum maintenance required
- ✓ Safety and reliability
- ✓ PBT roller holder
- ✓ DELRIN roller (self-lubricating )



### OPTIONAL

- ✓ ON / OFF switch
- ✓ SCHUKO plug

	DESCRIPTION	
	Standard Material	Upon Request
<b>Standard Version</b>		
Box	PP	-----
Roller	DELRIN	-----
Tube	Santoprene	Silicon
Power Supply	230 V 50 – 60 Hz	-----
Consumption	35 Watt	-----
Net Weight	0,5 kg.	-----
Ring Nuts	PP 1/8"	-----
Fittings	PP 4 x 6 mm	-----
	<b>DETERGENT KIT</b>	
	<b>DETERGENT</b>	<b>RINSE</b>
Suction tube	PVC 4 x 6	PVC 4 x 6
Delivery Tube	PVC 4 x 6	PE 4 x 6
Injection fitting	PP 90°	1/8" AISI
Foot filter	SS rubber holder	SS rubber holder

# PERISTALTIC PUMP MP2-B 1 TIMER

Data  
Sheet

TECHNICAL SPECIFICATIONS											
Standard	Max l/h	Pressure		Max cc / min	Tube	Dimensions	Box	Power [Watt]	RPM	Weight	
		Bar	PSI							kg.	Lbs
<b>230Vac VERSION</b>											
1,5 - 01	1,5	01	14,7	25	Santoprene	5,8 x 9,4	PP	35	10	0,5	1,2
04 - 01	04	01	14,7	66,67	Santoprene	5,8 x 9,4	PP	35	40	0,5	1,2
06 - 01	06	01	14,7	100	Santoprene	5,8 x 9,4	PP	35	40	0,5	1,2
01 - 03	01	03	44,1	16,67	Silicone	5 x 10	PP	35	20	0,5	1,2
12 - 01	12	01	14,7	200	Santoprene	5,8 x 9,4	PP	35		0,5	1,2
20 - 01	20	01	14,7	334	Santoprene	5,8 x 9,4	PP	35		0,5	1,2

