

PERISTALTIC PUMP MP2-R 230VAC

Data
Sheet

DESCRIPTION

- ✓ Peristaltic pump with adjustable flow rate by trimmer
- ✓ Reinforced PP body
- ✓ Polycarbonate front panel
- ✓ Standard 230 Vac Power Supply
- ✓ 0-100% speed regulation
- ✓ 100 % Made in Italy
- ✓ CE approved

OPTIONAL

- ✓ ON / OFF switch
- ✓ SCHUKO plug



DESCRIPTION		
	Standard Material	Upon Request
Standard Version		
Box	PP	-----
Roller	DELRIN	-----
Tube	Santoprene	Silicon
Power Supply	230 V 50 – 60 Hz	-----
Consumption	35 Watt	-----
Net Weight	0,5 kg.	-----
Ring Nuts	PP 1/8"	-----
Fittings	PP 4 x 6 mm	-----
Standard Version	230 Vac	24 VCC
DETERGENT KIT		
	DETERGENT	RINSE AID
Suction tube	PVC 4 x 6	PVC 4 x 6
Delivery tube	PVC 4 x 6	PE 4 x 6
Injection fitting	PP 90°	1/8" AISI
Foot filter	AISI Rubber Holder	AISI Rubber Holder

PERISTALTIC PUMP MP2-R 230 VAC

Data
Sheet

SPECIFICHE TECNICHE											
Standard	Max l/h	Pressure		Max cc / min	Tube	Tube dimensions	Pump Head	Power [Watt]	RPM	Weight	
		Bar	PSI							kg.	Lbs
VERSION 230 Vac											
1,5 - 01	1,5	01	14,7	25	Santoprene	5,8 x 9,4	PP	35	10	0,5	1,2
04 - 01	04	01	14,7	66,67	Santoprene	5,8 x 9,4	PP	35	30	0,5	1,2
06 - 01	06	01	14,7	100	Santoprene	5,8 x 9,4	PP	35	50	0,5	1,2
01 - 03	01	03	44,1	16,67	Silicone	5 x 10	PP	35	10	0,5	1,2
02 - 03	02	03	44,1	33,33	Silicone	5 x 10	PP	35	20	0,5	1,2
01 - 02	1,7	02	29,4	28,33	Tygon	6,4 x 9,5	PP	35	10	0,5	1,2
01 - 03	01	03	44,1	16,67	Santoprene	4,8 x 9,6	PP	35	10	0,5	1,2
02 - 03	2	03	44,1	33,4	Santoprene	4,8 x 9,6	PP	35	20	0,5	1,2

