

# PERISTALTIC PUMP

## MP3

Data  
Sheet

### DESCRIPTION

- ✓ Peristaltic pump with fixed flow rate
- ✓ Reinforced PP body
- ✓ Polycarbonate front panel
- ✓ Standard Power Supply 230 Vac
- ✓ 100 % Made in Italy
- ✓ CE approved
- ✓ Small size
- ✓ Easy to install and minimum maintenance required
- ✓ Safe and reliable
- ✓ PBT roller holder
- ✓ DELRIN roller (self-lubricating)



DESCRIPTION		
	Standard material	Upon request
<b>Standard version</b>		
Box	PP	-----
Roller	DELRIN	-----
Tube	Santoprene	Silicon / Tygon
Consumption	35 Watt	-----
Net Weight	0,35 kg.	-----
Ring Nuts	PP 1/8"	-----
Fittings	PP 4 x 6 mm	Rubber holder Hostaform
Power roller	230 Vac	24 Vdc

# PERISTALTIC PUMP MP3

Data  
Sheet

SPECIFICATIONS											
Standard	Max l/h	Pressure		Max cc / min	Tube	Dimensions	Box	Power [Watt]	RPM	Weight	
		Bar	PSI							kg.	Lbs
<b>230 Vac VERSION</b>											
1,5 - 01	1,5	01	14,7	25	Santoprene	5,8 x 9,4	PP	35	10	0,35	0,8
03 - 01	03	01	14,7	50	Santoprene	5,8 x 9,4	PP	35	20	0,35	0,8
04 - 01	04	01	14,7	66,67	Santoprene	5,8 x 9,4	PP	35	40	0,35	0,8
0,5 - 03	0,5	03	44,1	8,34	Silicone	5 x 10	PP	35	10	0,35	0,8
01 - 03	01	03	44,1	16,67	Silicone	5 x 10	PP	35	20	0,35	0,8
<b>24 Vdc VERSION</b>											
04 - 01	04	01	14,7	66,67	Santoprene	5,8 x 9,4	PP	35	40	0,35	0,8
06 - 01	06	01	14,7	100	Santoprene	5,8 x 9,4	PP	35	40	0,35	0,8
12-01	12	01	14,7	200	Santoprene	5,8 x 9,4	PP	35		0,35	0,8
16-01	16	01	14,7	267	Santoprene	5,8 x 9,4	PP	35		0,35	0,8
20-01	20	01	14,7	334	Santoprene	5,8 x 9,4	PP	35		0,35	0,8

